



Europäisches Patentamt
European Patent Office
Office européen des brevets



Publication number: **0 559 109 A1**

12

EUROPEAN PATENT APPLICATION

21 Application number: **93103182.7**

51 Int. Cl.⁵: **H01G 9/02, H01G 9/00,
H01G 9/05**

22 Date of filing: **27.02.93**

30 Priority: **02.03.92 JP 44676/92**

43 Date of publication of application:
08.09.93 Bulletin 93/36

84 Designated Contracting States:
DE FR GB

71 Applicant: **E.I. DU PONT DE NEMOURS AND
COMPANY**
1007 Market Street
Wilmington Delaware 19898(US)

72 Inventor: **Inaba, Akira**
3-22-5, 22-13-405 Kirigaoka, Midori-ku
Yokohama-shi, Kanagawa-ken 227(JP)

74 Representative: **von Kreisler, Alek et al**
Patentanwälte von Kreisler-Selting-Werner,
Postfach 10 22 41, Bahnhofsvorplatz 1
D-50462 Köln (DE)

54 **Tantalum solid electrolytic capacitor.**

57 To provide a tantalum solid electrolytic capacitor which enables to prevent a short-circuit due to diffusion of metals component contained in conductive polymer resin layer forming the cathode. A tantalum solid electrolytic capacitor comprising a fluorocarbon resin layer or a fluorocarbon resin containing layer being disposed between an anode composed of sintered tantalum having a surface of a dielectric oxide film and a cathode composition formed from a metal-containing conductive polymer resin composition, which may contain such fluorocarbon resin therein.

EP 0 559 109 A1